

POWER BUGGIES and COMPACT UTILITY LOADERS



Allen AT 14S

The all new AT14S rubber track concrete buggy delivers excellent performance and precise maneuverability. Equipped with a 90-degree dump angle and 180-degree pivoting dump this buggy can place your material exactly where you need it.

Allen AR16

The sixteen cubic foot AR16 Propane Power Buggy is perfect for indoor job sites where air quality is an concern. This factory installed propane system is perfect for helping avoid job stoppages or potential fines due to air quality regulations.

Toro Dingo TX 1000 Utility Loaders

The Dingo TX 1000 is equipped with Toro exclusive vertical lift loader arms, 1,000-lb rated operating capacity delivers category crushing performance. The TX 1000 also offers outstanding hinge pin height of 81" (206 cm) to clear the side of 30-yard dumpsters and one-ton trucks for maximum job site productivity.



AT14S Buggy

Description	
Engine	Honda GX630 (688 cc)
Horsepower Class	20 hp
Starter	Electric
Fuel Type	Gasoline
Fuel Capacity	3 gallons
Top Speed	Work: 4 mph (6 kph) Travel: 6 mph (10 kph)
Payload	1,785 lbs
Bucket Capacity	14 cu ft
Dump Angle	90-degrees
Pivot Angle	180-degrees
Weight	1,540 lb
Overall Dimensions (L X W X H)	98.4" x 33.3" x 54"



AR16 Propane Power Buggy

Description	
Engine	Honda GX390 (389 cc)
Horsepower Class	13 hp
Starter	Electric
Fuel Type	Propane
Fuel Capacity	8 gallons
Top Speed	7 mph
Payload	2,500 lbs
Bucket Capacity	16 cu ft
Lift Cylinder Diameter	2"
Dump / Return Speed Empty	5 Seconds
Wheelbase	40"
Weight	1,370 lb
Overall Dimensions (L X W X H)	97" x 47" x 64"



Dingo TX 1000 Wide Track

Engine		
Engine	Kubota® D1305 Diesel	
Air Filter	Two-stage, heavy-duty, remote	
Cooling System	Liquid Cooled	
Fuel Tank	11.5 gallons	
Oil Capacity	6.0 quarts	
Hydraulic System		
Hydraulic Pressure	3,000 PSI	
Hydraulic Flow	Traction: 13.3 gpm (each pump) Auxiliary: 15.2 gpm	
Reservior Capacity	15.2 gallons	
Tracks		
Standard	Sprocket-drive, 6 road wheels per side	
Traction	Dual hydrostatic pump	
Dimensions		
Track Width	127.6" x 5.9"	127.6" x 9.5"
Wheelbase	41"	
Ground Clearance	6.0"	
Overall Dimensions (WxLxH) With Bucket	33.7" x 100.7" x 53.2"	41" x 100.7" x 53.2"
Overall Dimensions (WxLxH) Without Bucket	33.7" x 81.7" x 53.2"	41" x 81.7" x 53.2"
Maximum Operating Height	105"	
Hinge Pin Height	81"	
Dump Height	61"	
Dump Angle	40-degrees	
Reach - Fully Raised	24.5"	
Ground Speed	4.7 mph	
Weight	2,610 lbs	2,790 lbs
Tip Capacity	2,857 lbs	3,071 lbs
Rated Operating Capacity (35% of Tip Capacity)*	1,000 lbs	1,075 lbs
Ground Pressure	5.5 PSI	3.6 PSI

*SAE J818 Rating of 35%

*Want to learn more about this equipment?
Contact your Able Tool and Equipment sales representative today!*

ABLE
TOOL and EQUIPMENT

abletool.net

410 Burnham St.
South Windsor, CT 06074
860-289-2020

149 Rocus St.
Springfield, MA 01104
413.363.0780